

SAFETY DATA SHEET

Creation Date 24-Nov-2010

Revision Date 19-Jan-2018

Revision Number 4

1. Identification

Product Name

Ethanol, denat. with 2-PrOH and MeOH

Cat No. :

AC224090000; AC224090010; AC224095000

Synonyms

Alcohol; Ethyl alcohol

Recommended Use Uses advised against Laboratory chemicals. Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

<u>Company</u>

Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100 Acros Organics One Reagent Lane Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US:**001-201-796-7100 / **Europe:** +32 14 57 52 99 **CHEMTREC** Tel. No.**US:**001-800-424-9300 / **Europe:**001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2	
Acute oral toxicity	Category 4	
Acute dermal toxicity	Category 4	
Acute Inhalation Toxicity - Vapors	Category 4	
Serious Eye Damage/Eye Irritation	Category 2	
Specific target organ toxicity (single exposure)	Category 1	
Target Organs - Optic nerve.		
Specific target organ toxicity - (repeated exposure)	Category 1	
Target Organs - Liver, Kidney.		

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor Harmful if swallowed Harmful in contact with skin Causes serious eye irritation Harmful if inhaled May cause drowsiness or dizziness Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. **WARNING.** Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Ethyl alcohol	64-17-5	90
Methyl alcohol	67-56-1	5
Isopropyl alcohol	67-63-0	5

4. First-aid measures			
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.		
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.		
Inhalation	Remove from exposure, lie down. Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention.		
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately.		
Most important symptoms and effects Notes to Physician	Breathing difficulties. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting Treat symptomatically		
	5. Fire-fighting measures		
Suitable Extinguishing Media	Water spray. Carbon dioxide (CO 2). Dry chemical. Chemical foam. Cool closed containers exposed to fire with water spray.		
Unsuitable Extinguishing Media	No information available		
Flash Point	12 °C / 53.6 °F		
Method -	No information available		
Autoignition Temperature	370 °C / 698 °F		
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	19.00% 4.00% t No information available No information available		

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<u>NFPA</u>	Health 3	Flammability 3	Instability 0	Physical hazards N/A
6. Accidental release measures				
Personal Precautions			n. Use personal protective equip y measures against static disch	
Environmental Precautions		See Section 12 for addition		-

Methods for Containment and Clean Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage				
Handling	Avoid contact with skin and eyes. Do not breathe dust. Do not breathe vapors or spray mist. Take precautionary measures against static discharges. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Wash hands before breaks and immediately after handling the product.			
Storage	Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat and sources of ignition. Flammables area.			

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl alcohol	Ethyl alcohol STEL: 1000 ppm		IDLH: 3300 ppm	TWA: 1000 ppm
		(Vacated) TWA: 1900 mg/m ³	TWA: 1000 ppm	TWA: 1900 mg/m ³
		TWA: 1000 ppm	TWA: 1900 mg/m ³	
		TWA: 1900 mg/m ³		
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m ³	TWA: 200 ppm	TWA: 260 mg/m ³
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m ³	STEL: 250 ppm
		(Vacated) STEL: 325 mg/m ³	STEL: 250 ppm	STEL: 310 mg/m ³
		Skin	STEL: 325 mg/m ³	
		TWA: 200 ppm		
		TWA: 260 mg/m ³		
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm	TWA: 400 ppm
	STEL: 400 ppm	(Vacated) TWA: 980 mg/m ³	TWA: 400 ppm	TWA: 980 mg/m ³
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m ³	STEL: 500 ppm
		(Vacated) STEL: 1225	STEL: 500 ppm	STEL: 1225 mg/m ³
		mg/m ³	STEL: 1225 mg/m ³	
		TWA: 400 ppm	-	
		TWA: 980 mg/m ³		

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.		
Personal Protective Equipment			
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.		
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.		
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.		

Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. Physical and chemical properties				
Physical State	Liquid			
Appearance	Colorless			
Odor	No information available			
Odor Threshold	No information available			
рН	No information available			
Melting Point/Range	-114 °C / -173.2 °F			
Boiling Point/Range	78 °C / 172.4 °F @ 760 mmHg			
Flash Point	12 °C / 53.6 °F			
Evaporation Rate	No information available			
Flammability (solid,gas)	Not applicable			
Flammability or explosive limits				
Upper	19.00%			
Lower	4.00%			
Vapor Pressure	59 mbar @ 20 °C			
Vapor Density	1.59			
Specific Gravity	0.780			
Solubility	No information available			
Partition coefficient; n-octanol/water	No data available			
Autoignition Temperature	370 °C / 698 °F			
Decomposition Temperature	No information available			
Viscosity	1.2 mPa.s at 20 °C			
Molecular Formula	C2 H6 O			
Molecular Weight	46.06			

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.
Incompatible Materials	Acids, Ammonia, Peroxides, Acid anhydrides, Acid chlorides, Metals, Reducing agents
Hazardous Decomposition Product	s Carbon monoxide (CO), Carbon dioxide (CO2)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information
Oral LD50
Dermal LD50

Category 4. ATE = 300 - 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Category 4. ATE = 1000 - 2000 mg/kg. Category 4. ATE = 10 - 20 mg/l.

Vapor LC50 Component Information

Component	Component LD50 Oral		LC50 Inhalation		
Ethyl alcohol	Ethyl alcohol 3450 mg/kg (Mouse)		20000 ppm/10H (Rat)		
Methyl alcohol	Calc. ATE 60 mg/kg LD50 > 1187 – 2769 mg/kg (Rat)	Calc. ATE 60 mg/kg LD50 = 17100 mg/kg(Rabbit)	Calc. ATE 0.6 mg/L (vapours) or 0.5 mg/L (mists) LC50 = 128.2 mg/L (Rat) 4 h		
Isopropyl alcohol	5840 mg/kg (Rat)	13900 mg/kg (Rat)	72.6 mg/L (Rat)4 h		

				0 mg/kg (Rabbit)		
Toxicologically Syn Products	•	No information ava				
Delayed and immed	liate effects as w	ell as chronic effe	cts from short an	d long-term expo	sure	
Irritation		May cause eye, sk	May cause eye, skin, and respiratory tract irritation			
Sensitization		No information ava	ilable			
Carcinogenicity		The table below inc	dicates whether ea	ich agency has list	ed any ingredient	as a carcinogen.
Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Group 1	Known	A3	Х	Not listed
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed
Isopropyl alcohol	67-63-0	Not listed	Not listed	Not listed	Not listed	Not listed
Mutagenic Effects		No information ava	ilable			
Reproductive Effect		No information available.				
Developmental Effe Teratogenicity	CIS	No information available. Teratogenic effects have occurred in experimental animals.				
STOT - single expos STOT - repeated exp		Optic nerve Liver Kidney				
Aspiration hazard		No information available				
Symptoms / effects,both acute and delayed		Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting				
Endocrine Disrupto	r Information	No information available				
Other Adverse Effect	cts	See actual entry in RTECS for complete information.				

12. Ecological information

Ecotoxicity

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l	Fathead minnow	Photobacterium	EC50 = 9268 mg/L/48h
	(Chlorella vulgaris)	(Pimephales promelas)	phosphoreum:EC50 = 34634	EC50 = 10800 mg/L/24h
		LC50 = 14200 mg/l/96h	mg/L/30 min	
			Photobacterium	
			phosphoreum:EC50 = 35470	
			mg/L/5 min	
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	
			EC50 = 43000 mg/L 5 min	
Isopropyl alcohol	EC50: > 1000 mg/L, 72h	LC50: > 1400000 µg/L, 96h	= 35390 mg/L EC50	13299 mg/L EC50 = 48 h
	(Desmodesmus	(Lepomis macrochirus)	Photobacterium	9714 mg/L EC50 = 24 h
	subspicatus)	LC50: = 9640 mg/L, 96h	phosphoreum 5 min	
	EC50: > 1000 mg/L, 96h	flow-through (Pimephales		
	(Desmodesmus	promelas)		
	subspicatus)	LC50: = 11130 mg/L, 96h		
		static (Pimephales		
		promelas)		

Persistence and Degradability

ity Persistence is unlikely based on information available.

Bioaccumulation/Accumulation

No information available.

Mobility

Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Isopropyl alcohol	0.05

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

	14. Transport information
DOT	
UN-No	UN1987
Proper Shipping Name	ALCOHOLS, N.O.S
Hazard Class	3
Packing Group	II
<u>TDG</u>	
UN-No	UN1987
Proper Shipping Name	ALCOHOLS, N.O.S
Hazard Class	3
Packing Group	II
IATA	
UN-No	UN1987
Proper Shipping Name	ALCOHOLS, N.O.S
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1987
Proper Shipping Name	ALCOHOLS, N.O.S
Hazard Class	3
Packing Group	

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethyl alcohol	Х	Х	-	200-578-6	-		Х	Х	Х	Х	Х
Methyl alcohol	Х	Х	-	200-659-6	-		Х	Х	Х	Х	Х
Isopropyl alcohol	Х	Х	-	200-661-7	-		Х	Х	Х	Х	Х

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	5	1.0
Isopropyl alcohol	67-63-0	5	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	Х		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs	
Methyl alcohol	5000 lb	-	
California Proposition 65 This produc	This product contains the following proposition 65 chemicals		

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic	-	Developmental
		beverages only)		Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl alcohol	Х	Х	Х	Х	Х
Methyl alcohol	Х	Х	Х	Х	Х
Isopropyl alcohol	X	Х	X	-	Х

U.S. Department of Transportation

Reportable Quantity (RQ):	Ν
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

No information available

	16. Other information
Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date	24-Nov-2010

19-Jan-2018

Revision Date
Print Date
Revision Summary

19-Jan-2018 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS