

Technical Data Sheet

PRODUCT FEATURES

- Interior Use Only
- 12 Years of Durability
- Good Coverage
- Durable and Washable
- Ideal For Kitchens & Baths
- Soap and Water Clean-Up
- GreenWise® Certified

RECOMMENDED USE

Ideal for interior surfaces requiring a durable semi-gloss finish. Excellent for kitchens, bathrooms, laundry rooms, children's rooms and other hard-use areas where a washable, semi-gloss finish is desired. Use on properly prepared plaster, drywall, wood masonry, plywood and properly primed metal.

RECOMMENDED APPLICATION**New Surfaces:****New Wood:**

272A101 – Royal Interiors Multi-Purpose Alkyd Primer

101A103 – Royal Interiors Multi-Purpose Latex Primer

New Plaster:

Aged for 30 days – 215A100 – Royal Int/Ext Stain Blocking Primer/Sealer

Aged for 90 days – 272A101 – Royal Interiors Multi-Purpose Alkyd Primer

New Drywall:

214A100 – Royal Interiors Drywall Primer

Masonry:

215A100 – Royal Int/Ext Stain Blocking Primer/Sealer

Metal:**Ferrous Metal:**

190A140 – Rust Stop Primer Red

190A141 – Rust Stop Primer Gray

Non-Ferrous Metal:

155A100 – Galvanized & Aluminum Primer

See Surface Preparation Section on label.

EQUIPMENT**Conv. Spray:** Use Sprayer Manufacturers Recommendations**Airless Spray:** Use Sprayer Manufacturers Recommendations**Brush:** Ace quality nylon/polyester brush**Roller:** 3/8" Nap Cover**Pad:** Standard**THINNER & CLEAN-UP**

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

LIMITATIONS

- Do not apply when air, surface or product temperature is below 50° F (10° C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90° F (32° C).

PACKAGING

Quarts, Gallons, 5 Gallon

COLORS

Ready Mix Colors & Tint Bases

NOTES

Product has not been certified to meet any federal specification.

SPECIFICATION DATA

Type:	Acrylic Latex
Finish:	Semi-Gloss
Gloss	45 - 50 @ 60°
% Solids:	
By Weight:	43 ± 2%
By Volume:	29 ± 2%
Wt. /Gallon:	10.46 lbs. ± 0.1
Flashpoint:	N/A
VOC lbs. /gal (max):	0.42
VOC g/L (max):	50
Thinner:	Water
Clean-up:	Soap and Water
Dry Time:	
To Touch:	½ hour
To Recoat:	2 - 4 hours
To Service:	Overnight
Thickness:	
Dry:	1.2 mil
Wet	4.0 mil
Coverage:	400 sq. ft./gal (on smooth surfaces)
Flame Spread Rate:	Class A (0-25 on non-combustible surfaces)

Note: Values are reported for High Hiding White and will vary depending on color.

The technical information is true and accurate to the best of our knowledge, but is subject to change without prior notice.