

## **SAFETY DATA SHEET**

**Issuing Date:** 06/25/2015 **Revision Date:** 06/25/2015

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product name: PURPLE GUARD Battery Protector

Recommended use of the chemical

and restrictions on use

Product code 891.525

Product Type Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use Battery Protectant.
Uses advised against No information available

Manufactured For: Winzer Corporation

4060 E. Plano Parkway

Plano, TX 75074

Company Phone Number: 800-527-4126

Emergency telephone number

24 Hour Emergency Number: INFOTRAC 1-800-535-5053 (USA & Canada)

WINZER

Page 1 / 10

### 2. HAZARDS IDENTIFICATION

#### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### DANGER

#### Hazard Statements

Causes skin irritation

Causes eye irritation

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

May cause damage to organs (Central Nervous System, Eyes, Kidney, Peripheral Nervous System, Respiratory System, and Skin) through prolonged or repeated exposure.

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance opaque Physical state Aerosol Odor Solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

WINZER.

\_\_\_\_\_

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

TE INTALED. Remove person to fresh all and keep conflictable in

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

None

#### Other information

· Harmful to aquatic life with long lasting effects

0.2170153% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # 110-54-3, HEXANE, MAY BE SUBSTITUTED FOR CAS # 64742-49-0, COMMERCIAL HEXANES.

Chemical Name	CAS-No	Weight %*
HEXANE	64742-49-0	40-50
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	10-20
HYDROTREATED HEAVY NAPHTHENIC	64742-48-9	1-10
PETROLEUM DISTILLATES	8052-41-3	1-10
ORGANOPHOSPATE ESTER,ZINC SALT	68649-42-3	0.1-1
XYLENE	1330-20-7	0.1-1

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. If symptoms persist, call a physician.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen

may be necessary. If breathing has stopped, contact emergency medical services

immediately.

**Ingestion** Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

Never give anything by mouth to an unconscious person. Risk of product entering the lungs

on vomiting after ingestion.



### Most important symptoms/effects, acute and delayed

**Main Symptoms** Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May be harmful

if swallowed.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

#### **Suitable Extinguishing Media**

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

### Specific hazards arising from the chemical

Flammable or extremely flammable aerosol. Container may burst in fire.

#### **Explosion Data**

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

#### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Absorb with sand, clay, or other suitable material. Hard Personal precautions

> surfaces may be mopped with water. Remove all sources of ignition. Avoid contact with the skin and the eyes. Evacuate personnel to be safe areas. Keep people away from and upwind of spill/leak. Contents under pressure. Do not puncture or incinerate cands. Wear

protective gloves/clothing and eye/face protection.

#### **Environmental precautions**

Report spills as required by local and federal regulations. Beware of vapors accumulating to **Environmental precautions** 

form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary

sewer system. Should not be released into the environment.

#### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Absorb or cover with dry earth, sand or

other non-combustible material and transfer to containers.

Contain liquid and collect with an inter.non-combustible material. Pick up and transfer to Methods for cleaning up

properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from

entering drains. Take precautionary measures against static discharges.

### 7. HANDLING AND STORAGE

#### Precautions for safe handling



Advice on safe handling

Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid contact with skin and eyes. Avoid breathing vapors or mist. DO not puncture or incinerate container. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Do not lay on its side. Store in a cool place.

#### Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

**Incompatible products** Store away from strong oxidizers and acids.

Aerosol Level 3

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HEXANE 64742-49-0	TWA: 50 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 500 ppm TWA: 1800 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m³
PETROLEUM DISTILLATES 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Exposure controls** 

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin and body protection** Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

\_<u>\_\_\_</u>\_\_



#### Physical and chemical properties

Physical state Aerosol Appearance opaque

AppearanceopaqueOdorSolvent

ColorOdor ThresholdNo information available

Based on propellant

Not applicable

Property Values Remarks • Methods

pH
 Melting/freezing point
 Boiling point/boiling range
 No information available
 No information available

Flash Point -104 °C / -155 °F
Evaporation rate No information available

Flammability (solid, gas)

No information available
No information available

Flammability Limits in Air

upper flammability limit<br/>lower flammability limitNo information available<br/>No information available<br/>No information availableVapor pressureNo information availableVapor densityNo information available

Specific Gravity 0.690

Water solubility Practically insoluble
Partition coefficient: n-octanol/waterNo information available
Autoignition temperature No information available

Decomposition temperatureNo information availableViscosityNo information availableExplosive propertiesNo information available

**Other information** 

VOC Content(%) 77.69

### 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible Materials**

Store away from strong oxidizers and acids.

#### **Hazardous Decomposition Products**

Carbon oxides.

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness

based on components. May cause irritation of respiratory tract. Avoid breathing vapors or

mists.

**Eye contact** Irritating to eyes. Avoid contact with eyes.

·\_\_\_\_\_



**Skin contact** Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin

contact may defat the skin and produce dermatitis. Avoid contact with skin.

Ingestion May be harmful or fatal if swallowed. Aspiration into the lungs during swallowing may

cause serious lung damage which may be fatal.

**Component Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXANE	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
64742-49-0			
HYDROTREATED HEAVY NAPHTHENIC 64742-48-9	> 5000 mg/kg(Rat)	> 3160 mg/kg(Rabbit)	-
XYLENE 1330-20-7	= 3500 mg/kg(Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h

#### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea,and

vomiting. Irritating to skin and eyes. Prolonged or repeated exposure may cause dermatitis. Aspiration into the lungs during swallowing may cause serious lung damage which may be

fatal.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Irritating to skin.

Sensitization No information available.

Germ Cell Mutagenicity No information available.

**Carcinogenicity**The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE	-	Group 3	-	-
1330-20-7				

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans Group 1 - Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

**Reproductive toxicity** Suspected of damaging fertility or the unborn child.

Specific target organ systemic toxicity (single exposure)
Specific target organ systemic toxicity (repeated exposure)

May cause drowsiness and dizziness. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Chronic toxicity Intentional misuse by fatal. Chronic hydroca

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest.

Target Organ Effects Central nervous system, Eyes, Kidney, Peripheral Nervous System (PNS), Respiratory

system, Skin.

**Aspiration hazard** May be fatal if swallowed and enters airways.

#### Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.2170153% of the mixture consists of ingredient(s) of unknown toxicity

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
			microorganisms	other aquatic invertebrates





NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
HYDROTREATED HEAVY NAPHTHENIC 64742-48-9	-	2200 mg/L LC50 Pimephales promelas 96h	-	-
ORGANOPHOSPATE ESTER,ZINC SALT 68649-42-3	-	1.0 - 5.0 mg/L LC50 Pimephales promelas 96h static 10.0 - 35.0 mg/L LC50 Pimephales promelas 96h semi-static	-	1 - 1.5 mg/L EC50 Daphnia magna 48h
XYLENE 1330-20-7	-	13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 13.4 mg/L LC50 Pimephales promelas 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio	-	0.6 mg/L LC50 Gammarus lacustris 48h 3.82 mg/L EC50 water flea 48h

### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical Name	log Pow
XYLENE	3.15
1330-20-7	

Other adverse effects No information available

### 13. DISPOSAL CONSIDERATIONS

### **Waste treatment**

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations. This material, as

supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

### 15. REGULATORY INFORMATION

#### **International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HEXANE	Х	Х	Х	Х	Х	Х	Х	Х
NAPHTHENIC OIL, SEVERLY HYDROT	Х	Х	X	Х	Х	Х	Х	Х
HYDROTREATED HEAVY NAPHTHENIC	Х	Х	X	Х	Х	Х	Х	Х
PETROLEUM DISTILLATES	Х	Х	Х	Х	Х	Х	Х	Х
ORGANOPHOSPATE ESTER,ZINC SALT	Х	Х	Х	Not listed	Х	Х	Х	Х
XYLENE	Х	Х	Х	Х	Х	Х	Х	Х

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
ORGANOPHOSPATE ESTER,ZINC SALT - 68649-42-3	68649-42-3	0.1-1	1.0
XYLENE - 1330-20-7	1330-20-7	0.1-1	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ORGANOPHOSPATE ESTER,ZINC SALT 68649-42-3		Х		





XYLENE	100 lb		Х
1330-20-7			

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

### U.S. State Regulations

#### **California Proposition 65**

This product does not contain any known Proposition 65 chemicals.

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM DISTILLATES 8052-41-3	X	X	Х
ORGANOPHOSPATE ESTER,ZINC SALT 68649-42-3	Х		Х
XYLENE 1330-20-7	X	X	Х

**EPA Pesticide Registration Number** Not applicable

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

### **16. OTHER INFORMATION**

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical hazards 
HMIS Health Hazard 2\* Flammability 4 Physical Hazard 1 Personal protection B

Chronic Hazard Star Legend Chronic Health Hazard Repeated or prolonged exposure may cause central nervous system damage

Prepared By: Regualtory Affairs

Issuing date25-Jun-2015Revision Date25-Jun-2015

**Revision Note** 

No information available

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet** 



Page 10 / 10