



Becton Dickinson and Company

Material Safety Data Sheet

SECTION 1 – PRODUCT IDENTIFICATION

NAME Becton Dickinson Diabetes Care		ADDRESS One Becton Drive, Franklin Lakes, NJ 07417-1883	
TELEPHONE NUMBER (201) 847-7000	FOR ADDITIONAL INFORMATION CONTACT: 1-888-237-2762	DATE PREPARED May 20, 2009	
COMMON NAME (USED ON LABEL) 70% Isopropyl Alcohol Preps		CHEMICAL FAMILY Alcohol	
CHEMICAL NAME Isopropyl Alcohol		FORMULA (CH ₃) ₂ CHOH	
TRADE NAME & SYNONYMS BD Alcohol Swabs			

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENT	CAS #	%(WT)	TLV	PEL
Isopropyl Alcohol	67-63-0	70	980 Mg/M3	980 Mg/M3

PEL: Permissible Exposure Limit established by the Occupational Safety and Health Administration (OSHA).

TLV: Threshold Limit Value established by the American Conference of Governmental Industrial Hygienists, 1986-1987.

SECTION 3 – HAZARD IDENTIFICATION

Irritant (Xi) : R36 - Irritating to eyes.

Highly flammable (F) : R11 - Highly flammable.

Other : R67 - Vapors may cause drowsiness and dizziness.

PRIMARY ROUTES OF EXPOSURE
Skin, Eye, Inhalation or Ingestion

SIGNS AND SYMPTOMS OF EXPOSURE Direct contact with eyes may result in irritation. Target Organs: Eyes, skin and respiratory
(1) ACUTE OVEREXPOSURE tract.

(2) CHRONIC OVEREXPOSURE - Prolonged contact with skin may result in drying or irritation. Prolonged inhalation of vapors may cause slight headaches or dizziness. Prolonged exposure to vapors may result in eye irritation.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
Isopropyl alcohol is not a known liver or kidney toxin; persons with impaired liver or renal function should limit exposure.

CHEMICAL/COMPONENT LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN None	NTP ☐ Yes ☒ No	LARC ☐ Yes ☒ No	OSHA ☐ Yes ☒ No
---	--	---	---

OTHER EXPOSURE LIMITS None determined.

SECTION 4 – FIRST AID MEASURES

EMERGENCY & FIRST AID PROCEDURES:

EYE CONTACT: Flush with water for 15 minutes, seek medical attention.

SKIN CONTACT: Flush with water for 15 minutes.

INGESTION: Not likely; if ingestion occurs, do not induce vomiting, seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES			
FLASH POINT 12 degrees C (Isopropyl Alcohol 99%)		FLAMMABLE LIMITS IN AIR (% by Volume) LOWER: 2.0% UPPER: 12.7%	
EXTINGUISHING MEDIA Carbon Dioxide, alcohol foam or dry chemical		AUTO IGNITION TEMPERATURE 399 degrees C	
UNUSUAL FIRE AND EXPLOSION HAZARDS None			
SPECIAL FIRE FIGHTING PROCEDURES Use self-contained breathing apparatus when in close proximity to fire.			
SECTION 6 – ACCIDENTIAL RELEASE MEASURES			
8 STEPS TO BE TAKEN IN CASE MATERIAL IS LEAKED OR SPILLED Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition.			
WASTE DISPOSAL METHOD Dispose of in accordance with applicable local, state and federal laws.			
SECTION 7 – HANDELING AND STORAGE			
PRECAUTIONS TO BE TAKEN IN HANDLING & STORING Store away from heat and ignition sources.			
OTHER PRECAUTIONS Not determined.			
SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION			
RESPIRATORY PROTECTION Respiratory protection is not required under normal use.			
VENTILATION For normal use - use in a well ventilated area.			
PROTECTIVE GLOVES Not required under normal use.		EYE PROTECTION Not required under normal use.	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT Not required under normal use.			
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES			
BOILING POINT 82.4 degrees C		SPECIFIC GRAVITY (H ₂ O =1) .869 - .879 at 25 degrees C	VAPOR PRESSURE (mm Hg) 33mm at 20 degrees C
PERCENT VOLATILE BY VOLUME (%) 100%	VAPOR DENSITY (AIR =1) 2.07	EVAPORATION RATE (Butyl Acetate =1) 2.88	
SOLUBILITY IN WATER Soluble	REACTIVITY IN WATER Does not apply	FLASH POINT 12 degrees C (Isopropyl Alcohol 99%)	
APPEARANCE AND ODOR Saturated pad, colorless liquid with an alcohol odor.			
SECTION 10 – STABILITY AND REACTIVITY DATA			
STABILITY Unstable ☐ Stable ☒		CONDITIONS TO AVOID Sources of ignition, excessive heat	
INCOMPATIBILITY (MATERIALS TO AVOID) Strong Oxidizers, acetaldehyde chlorine, ethylene oxide, acids, isocyanates			
HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide, carbon dioxide.			
HAZARDOUS POLYMERIZATION May Occur ☐ Will not Occur ☒			
SECTION 11 – TOXICOLOGICAL INFORMATION			
PRECAUTIONS TO BE TAKEN IN HANDLING & STORING Store away from heat and ignition sources.			
OTHER PRECAUTIONS Not determined.			

SECTION 12 – ECOLOGICAL INFORMATION

Environmental Fate:

This product is classified as a Volatile Organic Component according to Directive 1999/13/EC.

Mobility : Product completely soluble in water.

Persistence and Degradability : Easily biologically degradable.

By major discharge of product in surface waters, a lack of oxygen may occur.

Bioaccumulation : Little chance on bioaccumulation.

* Ecotoxicity : Ecotoxic up to a small extent.

Weak water pollutant (WGK 1).

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal

State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 – TRANSPORTATION INFORMATION

Proper Shipping Name: ISOPROPANOL SOLUTION

Hazard Class: 3

UN/NA: UN1219

Packing Group: II

Containers of 1L or less may be shipped as Consumer Commodity ORM-D

SECTION 15 – REGULATORY INFORMATION

US FEDERAL

TSCA

CAS# 67-63-0 is listed on the TSCA inventory.

TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

CERCLA Hazardous Substances and corresponding RQs

None of the chemicals in this material have an RQ.

SARA Section 302 Extremely Hazardous Substances

None of the chemicals in this product have a TPQ.

SARA Codes

CAS # 67-63-0: immediate, delayed, fire.

Section 313

This material contains Isopropyl alcohol (CAS# 67-63-0, 70%), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA.

STATE

CAS# 67-63-0 can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, Massachusetts.

European/International Regulations

EC Number: 200-661-7

European Labeling in Accordance with EC Directives

Hazard Symbols:

XI F

Risk Phrases:

R 11 Highly flammable.

R 36 Irritating to eyes.

R 67 Vapors may cause drowsiness and dizziness.

Safety Phrases:

S 16 Keep away from sources of ignition - No smoking.

S 24/25 Avoid contact with skin and eyes.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 7 Keep container tightly closed.

SECTION 16 – OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate. However, neither Becton, Dickinson and Company nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.